



MINI VISION

Product Specification:

Antenna Impedence	□ □	50ohm
Transmitter Frequency	□ □	1.394 GHz
Tx Power Output	□ □	500mW(max)
Oscillator	□ □	PLL (Phase Locked Loop)
Channel Bandwidth	□ □	10MHz
Operating Temperature	□ □	-25 to +60°C
Video Input/Output	□ □	1V p-p
Audio Input/Output	□ □	50mVrms +/- 10% /600W
Modulation Technique	□ □	Frequency Modulation (FM)
Pre-emphasis	□ □	CCIR-PAL-405-01
Operating Voltage	□ □	12V d.c / 85-264 a.c
Protection	□ □	IP67
Range	□ □	12Km (Line of sight)
Tx module dimensions	□ □	246 x 118 x 70 mm
Tx module weight	□ □	2.3 kg
Tx control dimensions	□ □	168 x 100 x 97 mm
Tx control weight	□ □	1.7 kg
Rx module dimensions	□ □	198 x 95 x 33 mm
Rx module weight	□ □	1.0 kg
Rx control dimensions	□ □	240 x 180 x 90 mm
Rx control weight	□ □	3.6 kg
Rx system in case	□ □	370 x 330 x 280 mm
Rx system in case-weight	□ □	12 kg
Whole system in case dims	□ □	640 x 390 x 360 mm
Whole system in case weight	□ □	27 kg

CDL - Silverfield House - Claymore Drive
Aberdeen AB23 8GD - Scotland - UK
TEL: +44(0)1224 706655 - FAX: +44(0)1224 709840
EMAIL: info@cdltd.net - WEB: www.cdltd.net